



Base oil 6cst

Appearance	VISUAL	Bright and Clear	-	Bright and Clear
Density @15°C	ASTM D4052	Report	Kg/l	0.8470
	ASTM D1298	Report	Kg/l	-
Colour	ASTM D1500	0.5Max	-	L 0.5 ASTM Color
Kinematic Viscosity at 40°C	ASTM D445	Report	mm ² /s(cst)	35.19
Kinematic Viscosity at 100°C	ASTM D445	5.70-6.70	mm ² /s(cst)	6.256
Viscosity Index	ASTM D2270	121 Min	-	128
Pour Point	ASTM D97	-12 Max	°C	-
	ASTM D5950	-12 Max	°C	-15
Flash Point	ASTM D92	200 Min	°C	242
Evaporation Loss.Noak	ASTM D5800-B	9 Max	Wt %	6.4
Sulfur Content	ASTM D2622	Report	mg/kg (ppm wt)	<3
	ASTM D5453	Report	mg/kg (ppm wt)	-
Saturates	IP368	Report	Wt %	-
	ASTM D7419	Report	Wt %	99.4
Cold Cranking Simulation. ccs@ -30	ASTM D5293	Report	mPa.s(cp)	5043

Head Office Address: Unit 13, 4th floor , No 966, Minoram Building , Sharifi Square, Hasan Bana Street

2nd Address: Bazneshastegan Alley, Vafamanesh Street, Heravi Square

Phone number:+982121000501 +982121007364 +982121001445

  +989120039531

Factories:

1-Isfahan- Razi Industrial Estate

2- Isfahan- Koohpaye Industrial Estate

3-Ghazvin-charmsazi-Pasargad Industrial Estate

4-Tehran-Charm sazi Street-Eshtehard Industrial Estate

